



Emtek Ultrascap Cempoint Pointing Mortar 20kg Bag

EMTEK Streetscape Systems

Ultrascap Cempoint is a cementitious pointing mortar which conforms to the demands of BS7533. Ultrascap Cempoint is a gun applied cementitious mortar for the repointing of brickwork, blockwork and stone walling. It is also ideal for the repointing of concrete pavements, flags and slabs.



KEY FEATURES

- Conforms to BS7533
- Gun applied
- Fast and easy application
- Mixes quickly on site with water
- No priming required
- Good compatibility
- Excellent resistance to freeze thaw
- Wide range of colours available
- Economical
- Shrinkage compensated

PERFORMANCE

Pot Life	Initial Set	Final Set	Fresh Wet Density	Compressive Strength	Flexural Strength
45 minutes	3 hours	6 hours	2150 kg/m ³	49.6N/mm ² (28 days)	8.30N/mm ²

Adhesive/Bond Strength	Modulus of Elasticity	Shrinkage	Yield
1.22 N/mm ²	3 hours	6 hours	15 Litres / 20kg bag

Packaging

Emtek Ultrascap Cempoint is supplied in 20kg polythene lined bags delivered on shrink wrapped pallets.

Shelf Life

Store in a dry place at temperatures between 5°C - 35°C. Shelf life in correct conditions for sealed bags is 6 months. High temperatures and high humidity will lead to a reduced shelf life.

Colour

Natural Grey, Light Brown, Sandstone, Buff and York-stone.
NB. Special colours subject to lead-time, there may be colour variations between batches

Please Note: All tests are carried out at 20°C in temperature-controlled laboratories. Where temperatures are variable cementitious product performance will vary. Cool temperatures retard, warm temperatures accelerate.

Emtek Ltd
Woodland House, 7 Silverwood Industrial Area
Silverwood Road, Lurgan
Co. Armagh BT66 6LN

Telephone
+44 (0) 28 3834 8600
Facsimile
+44 (0) 28 3834 8601

Email
info@emtek.co.uk
Web
www.emtek.co.uk

EMTEK