



Emtek Ultrascape Pro-Prime BS7533 Slurry Primer 20kg Bag

EMTEK Streetscape Systems



Emtek Ultrascape Pro-Prime is a polymer modified cementitious slurry primer specifically formulated to provide an exceptional bond between all types of stone surface and Emtek Ultrascape Pro-Bed HS Fine Bedding Concrete. A good bond between layers is essential to combat the stresses imposed by ever increasing traffic on pavement surfaces. Correct use of this product ensures the minimum bond required for BS7533 between bedding concrete and stone is achieved.

KEY FEATURES

- Provides an exceptional bond between all types of stone surfaces
- User friendly, only requires the addition of water on site
- BS7533 compliant
- Complete system, no split liability
- Compatibility between layers

PERFORMANCE

Packaging	Yield	Standard Conformity	Open Time
20kg tripple walled paper bags	15m ² per 20kg bag approximately	BS7533 Part 12:2006	1 hour at 20°C

Storage

This product must be stored in unopened bags, clear of the ground in cool dry conditions at temperatures between 5°C and 30°C and protected from excessive drafts and frost. If stored correctly and used within 6 months of the date shown on the bag, the activity of the reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement.

Shelf Life

Shelf life in correct conditions for sealed bags from date of manufacture is 6 months. High temperatures and high humidity will lead to a reduced shelf life.

Water Required	Bond (Adhesion) Strength*
7 litres per 20kg bag	2.20 N/mm ² * Bond Strength when used in conjunction with Emtek Ultrascape Pro-Bed HS

Please Note: All tests are carried out at 20°C in temperature-controlled laboratories. Where temperatures are variable cementitious product performance will vary. Cool temperatures retard, warm temperatures accelerate.

Emtek Ltd
Woodland House, 7 Silverwood Industrial Area
Silverwood Road, Lurgan
Co. Armagh BT66 6LN

Telephone
+44 (0) 28 3834 8600
Facsimile
+44 (0) 28 3834 8601

Email
info@emtek.co.uk
Web
www.emtek.co.uk

EMTEK